

(12) **UK Patent Application** (19) **GB** (11) **2 383 061** (13) **A**

(43) Date of Printing by UK Office 18.06.2003

(21) Application No 0300314.2

(22) Date of Filing 04.07.2001

(30) Priority Data

(31) 00305968 (32) 13.07.2000 (33) EP

(86) International Application Data

PCT/EP2001/007691 En 04.07.2001

(87) International Publication Data

WO2002/006625 En 24.01.2002

(51) INT CL⁷

E21B 17/02 47/12

(52) UK CL (Edition V)

E1F FHK

(56) Documents Cited by ISA

EP 0964134 A

EP 0721053 A

US 5233304 A

(58) Field of Search by ISA

INT CL⁷ E21B

Other: Online: EPO-Internal, WPI Data, TULSA

(71) Applicant(s)

Shell Internationale Research Maatschappij B.V.
(Incorporated in the Netherlands)
Carel van Bylandtlaan 30, NL-2596 HR,
The Hague, Netherlands

(74) Agent and/or Address for Service

J M Overton
Shell International Limited,
Intellectual Property Services,
P.O.Box 662, LONDON, SE1 7NE,
United Kingdom


(72) Inventor(s)

Neil Griffiths

(54) Abstract Title

Deploying a cable through a guide conduit in a well

(57) A fibre optical or other cable is inserted through a pre-installed guide conduit in a well by: -installing an upper part of the guide conduit permanently in the well such that it is embedded in the annular cement body at the outer surface of a casing string between a wellhead and an outer component of a guide conduit connector which is located near a lower end of the casing string; -installing a lower part of the guide conduit in the well such that it extends alongside the outer surface or is an integral part of a liner string down from an inner component of the guide conduit connector which is located near an upper end of the liner string; -aligning the inner and outer components of the guide conduit connector with each other; and -pumping the cable down through the thus interconnected upper and lower parts of the guide conduit.



GB 2 383 061

THIS PAGE BLANK (USPTO)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 January 2002 (24.01.2002)

PCT

(10) International Publication Number
WO 02/06625 A1

(51) International Patent Classification⁷: **E21B 17/02**,
47/12

(71) Applicant (*for CA only*): **SHELL CANADA LIMITED**
[CA/CA]; 400 4TH Avenue S.W., Calgary, Alberta T2P
2H5 (CA).

(21) International Application Number: PCT/EP01/07691

(72) Inventor; and

(22) International Filing Date: 4 July 2001 (04.07.2001)

(75) Inventor/Applicant (*for US only*): **GRIFFITHS, Neil**
[GB/NL]; Volmerlaan 8, NL-2288 GD Rijswijk (NL).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
00305968.0 13 July 2000 (13.07.2000) EP


(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(71) Applicant (*for all designated States except CA, US*): **SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V.** [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

[Continued on next page]

(54) Title: DEPLOYING A CABLE THROUGH A GUIDE CONDUIT IN A WELL



(57) Abstract: A fibre optical or other cable is inserted through a pre-installed guide conduit in a well by: -installing an upper part of the guide conduit permanently in the well such that it is embedded in the annular cement body at the outer surface of a casing string between a wellhead and an outer component of a guide conduit connector which is located near a lower end of the casing string; -installing a lower part of the guide conduit in the well such that it extends alongside the outer surface or is an integral part of a liner string down from an inner component of the guide conduit connector which is located near an upper end of the liner string; -aligning the inner and outer components of the guide conduit connector with each other; and -pumping the cable down through the thus interconnected upper and lower parts of the guide conduit.

WO 02/06625 A1



patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

DEPLOYING A CABLE THROUGH A GUIDE CONDUIT IN A WELL

Background of the Invention

The invention relates to a method of deploying a fibre-optical cable or other power and/or signal transmission cable through a pre-installed guide conduit in a well.

It is known to pre-install a small guide conduit in the production tubing or in the production tubing/casing annulus of a well and to subsequently pump a fibre optical cable down through the guide conduit.

However, well equipment, such as a downhole electrical submersible pump (known as "ESP") or a downhole safety or control valve may make it difficult or even impossible to install such a guide conduit.

The present invention aims to overcome the difficulty of installing a fibre optical or other cable and guide conduit in a well which may contain equipment such as an ESP or downhole valves. The present invention also aims to install a guide conduit and cable such that the risk of damage to the cable during the lifetime of the well is minimized.

Summary of the Invention

The method according to the invention comprises the steps of:

- installing an upper part of the guide conduit permanently in the well such that it extends alongside the outer surface of a casing string between a wellhead and an outer component of a guide conduit connector which is located near a lower end of the casing string and which forms a port opening in the inner surface of the casing;

- 2 -

- installing a lower part of the guide conduit in the well such that it extends alongside the outer surface or is an integral part of the liner string down from an inner component of a guide conduit connector which is located near an upper end of the liner string and which forms a port opening in the outer surface of the liner;
- aligning the inner and outer components of the guide connector with each other; and
- inserting the power and/or signal transmission cable through the thus interconnected upper and lower parts of the guide conduit.

Accordingly the upper part of the guide conduit does not form an obstacle for any operation or maintenance activity in the well since the guide conduit is usually embedded in a cement body that fixes the casing in the wellbore and the cable contained in the guide conduit is well protected against damage.

Preferably, the outer component of the guide conduit connector forms a profiled tubular receptacle near the lower end of the casing string and the inner component of the guide conduit connector forms a profiled cylindrical surface on the outer surface of the liner near a liner hanger which in use is suspended within the casing and wherein the inner and outer components of the guide conduit connector are provided with orienting means to orient the inner component in a predetermined angular orientation within the outer component such that said port openings are in alignment with each other.

To enable a smooth insertion of the cable through the guide conduit it is preferred that the guide conduit only has a smooth curvature at the location of the guide conduit connector.

To this end it is preferred that the port openings of said inner and outer components of the guide conduit connector define in use a central axis which intersects a

longitudinal axis of the casing string and liner hanger assembly at an acute angle.

Description of a preferred embodiment

5 The invention will be described in more detail with reference to the accompanying Fig. 1, which is a longitudinal sectional view of a well which is equipped with a fibre optical cable and split guide conduit according to the invention.

10 The well shown in Fig. 1 has a wellhead 1 in which a casing 2 is suspended by means of a casing hanger 3. The casing 2 is cemented in the wellbore 4 by means of an annular body of cement 5.

15 The casing 2 is provided near its lower end with a profiled tubular receptacle 6 in which a profiled cylindrical inner component 7 of a guide conduit connector is suspended which forms part of a liner 8.

A sand screen 9 is arranged at the lower end of the liner 8 and in use oil, gas and/or water flows through the sand screen 9 into the liner 8.

20 A fibre optical cable 11 in which a set of multisensors (not shown) is incorporated for measuring pressure, temperature and composition of fluid flowing through the screen 9, passes through a guide conduit of which the upper end 12 passes through the annular cement body 5 surrounding the casing string 2. Alternatively the
25 fibre optical cable 11 itself forms a multisensor by virtue of the dependency of the light transmission characteristics of the cable 11 on pressure, temperature and fluid composition. In this way the entire length of
30 the well can be equipped with sensors for monitoring the said parameters.

The lower part 13 of the guide conduit extends between the inner component 7 of the guide conduit connector and the sand screen 9. The upper and lower
35 parts 12 and 13 of the guide conduit are interconnected

by the guide conduit connector 6, 7. The tubular outer component of the connector comprises a bore 14 in the tubular receptacle 6. The cylindrical inner component 7 of the connector comprises a bore 15.

5 The bore 14 in the outer component 6 of the guide conduit connector terminates as a port opening 16 in the cylindrical inner surface of the outer component 6 and the bore 15 in the inner component 7 of the connector terminates as a port opening 17 in the cylindrical outer
10 surface of said inner component 7.

 To ensure that the port openings 16 and 17 are aligned the inner component 7 of the guide conduit connector is equipped with a series of profiled dogs 18, which orient said inner component 7 automatically at a
15 pre-determined angular orientation inside the outer component 6.

 For the sake of clarity of the drawing a large annular spacing is shown between the inner and outer components 6 and 7 of the connector. However, it will be
20 understood that in practice this clearance will be minimal and be limited to less than a few millimetres only.

 In order to sealingly secure the liner 8 in the casing 2 a liner hanger and packer assembly 20 is
25 arranged at the upper end of the liner 8. Furthermore, sealing rings 21 are arranged at the upper and lower ends of the cylindrical outer surface of inner component 7 of the conduit connector to provide a fluid seal between the annulus present between the cylindrical surfaces of the
30 inner and outer components 6 and 7 of the guide conduit connector and the rest of the wellbore so that the fibre optical cable 11 can be easily pumped from the upper part 12 of the guide conduit via bores 14 and 15 in the guide conduit connector components 6 and 7 into the lower
35 part 13 of the guide conduit.

C L A I M S

1. A method of deploying a power and/or signal transmission cable through a pre-installed guide conduit in a well, the method comprising:

- 5 - installing an upper part of the guide conduit permanently in the well such that it extends alongside the outer surface of a casing string between a wellhead and an outer component of a guide conduit connector which is located near a lower end of the casing string and which forms a port opening in the inner surface of the casing;
- 10 - installing a lower part of the guide conduit in the well such that it extends alongside the outer surface or is an integral part of a well liner string down from an inner component of the guide conduit connector which is located near an upper end of the liner string and which forms a port opening in the outer surface of the liner;
- 15 - aligning the inner component with the outer component of the guide conduit connector; and
- 20 - inserting the power and/or signal transmission cable through the thus interconnected upper and lower parts of the guide conduit.

25 2. The method of claim 1, wherein the outer component of the guide conduit connector forms a profiled tubular receptacle near the lower end of the casing string and the inner component of the guide conduit connector forms a profiled cylindrical surface on the outer surface of the liner near a liner hanger which in use is suspended within the casing string and wherein the inner and outer components of the guide conduit connector are provided with orienting means to orient the inner component in a
30 predetermined angular orientation within the outer

component such that said port openings are in alignment with each other.

5 3. The method of claim 2, wherein the port openings of said inner and outer components of the guide conduit connector define in use a central axis which intersects a longitudinal axis of the casing string and liner hanger assembly at an acute angle.

4. The method of claim 1, wherein the power and/or signal transmission cable is a fibre optical cable.

1/1




Fig.1.

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 01/07691

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 E21B17/02 E21B47/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 E21B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, TULSA

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 721 053 A (SHELL INT RESEARCH) 10 July 1996 (1996-07-10) column 3, line 9 - line 32	1-4
A	EP 0 964 134 A (SCHLUMBERGER SERVICES PETROL ; SCHLUMBERGER TECHNOLOGY BV (NL); SCH) 15 December 1999 (1999-12-15) column 6, paragraph 26 - paragraph 27	1-4
A	US 5 233 304 A (HUBANS CHRISTIAN) 3 August 1993 (1993-08-03) column 3, line 29 - line 37	1-4

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

*** Special categories of cited documents :**

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

27 September 2001

Date of mailing of the international search report

04/10/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Garrido Garcia, M

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 01/07691

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0721053	A	10-07-1996	EP 0721053 A1	10-07-1996
			BR 9606966 A	04-11-1997
			CA 2208661 A1	11-07-1996
			DE 69600520 D1	17-09-1998
			DE 69600520 T2	28-01-1999
			DK 800614 T3	28-06-1999
			WO 9621085 A1	11-07-1996
			EP 0800614 A1	15-10-1997
			NO 973088 A	02-07-1997
			RU 2149261 C1	20-05-2000
			US 5745047 A	28-04-1998
EP 0964134	A	15-12-1999	GB 2338253 A	15-12-1999
			EP 0964134 A2	15-12-1999
			NO 992879 A	13-12-1999
US 5233304	A	03-08-1993	FR 2654521 A1	17-05-1991
			AT 96233 T	15-11-1993
			AU 644818 B2	23-12-1993
			AU 6581190 A	23-05-1991
			CA 2029938 A1	16-05-1991
			DE 69004059 D1	25-11-1993
			DK 433110 T3	07-03-1994
			EP 0433110 A1	19-06-1991
			NO 176334 B	05-12-1994
			OA 9271 A	31-08-1992

THIS PAGE BLANK (USPTO)